X-Head DOHC

Installation Guide



Fits 2010-2012 BMW R1200GS: 2013 ADV:

2010-2013 R1200RT; 2011-2014 R1200R; 2014+ R nineT

REV: 15 APR 15

Care Instructions:

Clean with soap and water. Armor-All works well to restore appearance. Parts: Left & Right Guards Left & Right Rubber Liners 6 - M6 Socket Head Cap Screws

Tools Required: 5mm Hex Driver Torque Wrench

6 - Washers

- ***** PLACE THE BIKE ON ITS CENTER STAND ON LEVEL GROUND
- ***** ALLOW THE ENGINE TO COOL BEFORE **DOING WORK**
- ***** PERFORM INSTALLATION AT ROOM **TEMPERATURE.** Cold temperatures can contract the X-Head materials making it more difficult to install.
- 1. Remove three existing fasteners from the sides of the cylinder heads.



- ***** IF THE RUBBER LINERS HAVE SHIFTED **POSITION DURING SHIPPING, RE-LOCATE** THEM ON THE POSTS INSIDE THE **GUARDS.**
- 2. Position an X-Head with rubber liner over the cylinder head, aligning the mounting holes with the bosses on the engine.
- 3. Loosely install three M6 Cap Screws with washers in the following sequence to prevent binding:
 - 3.1 Front
 - 3.2 Top rear
 - 3.3 Bottom rear

NOTE: After inserting the first screw half way by hand, push the X-Head against the cylinder to align the second holes and install the screw loosely. Aligning the third holes to insert the screw may require additional hand pressure.

4. Tighten screws with a Torque Wrench and a 5mm Hex Driver

Tightening torque 7lb/ft; 10 Nm **DO NOT OVER TIGHTEN**





WARNING AND DISCLAIMER: All parts manufactured, designed or sold by Machineart Moto ("MaMo") should be installed by a qualified motorcycle technician. The risk of injury is increased by improper installation or misuse of equipment. MaMo's customers must exercise good judgment in the use, control, alteration, part selection and installation, and maintenance of their motorcycles. In the event of a possible defect in material or design, or any other defect in a part manufactured, designed or sold by MaMo, the responsibility of MaMo is limited to a refund of the purchase price or the replacement of the part if MaMo determines the part to be defective, and subject to MaMo's inspection of the part within thirty (30) days from the date of purchase. (Note: any attempted repairs or modifications made to MaMo products will void this limited warranty). MaMo, under no circumstances will be responsible for incidental and/or consequential damages, property damage, personal injury damage, or damage, injury, cost or expense of any kind or nature whatsoever except as provided by law. MaMo makes no other warranty, express or implied, including without limitation any warranties of merchantability and fitness for a particular purpose.